



PREMO

PRIMACY 90 PARTITION

TECHNICAL DATA SHEET

Integral modular partition system with high sound reduction.

Demountable partition

No visible profiling

Reinstallation possibility

Normative applied reference UNE 41955



| | |
|-------------------|--|
| Thickness | 90 mm. |
| Acoustic | Of up to Rw 45 dB. |
| Module | Width standard 1200 mm, up to 8000mm for glazed panels. Height: up to 6000 mm. |
| Interior supports | Sendzimir galvanized steel 0,8 mm. Mechanical Properties EN 10346 Height regulation by machining bracing connector |
| Exterior profiles | Extruded aluminium in accordance EN-755 y EN-573-3 Anodised or lacquered aluminium Qualicoat requirements |
| Panels | 19 mm. woodchip hardboard panel decorative coated. Coating options: melamine, high pressure laminate, wood, textile, vinile... Panels hold by zetas and panel clips causing demountability possibility |
| Glass panes | Thickness of between 3+3 and 6+6 mm. Panes junction by fine transparent polycarbonate H |
| Doors | Thickness: 40mm. and 88 mm. flush door Possibility hidden frames and hinges Blind, pane o r mixed. Frame panel or rail. One or two panes framed |
| Interior | 75 mm. thick rock wool. AW 0.80. UNE EN 13162 for thermal and acoustic insulation |
| Panel joints | 3 mm. groove with aluminium profile |